

Digital Signage - Sparkle Series



10.1" LCD-based Dual Screen ESL

ZKS101-D

PRODUCT DATASHEET

PRODUCT FEATURES



Colorful dual screen, extraordinary design

- LCD full-color double-sided screen
- 14mm ultra-thin thickness, 7.17mm ultra-narrow border
- High resolution supports highly clear display



Refresh quickly & Support varied advertising strategies

- Display words, pictures, videos, website pages and other formats
- Support free combination playback of a variety of file formats
- 0.1s ultra-fast update, satisfying varied advertising strategies
- Super-rich templates library which can be infinitely expanded



Easily fit in various environments with high protection level

- Normal operation between 25±5°C
- IP65 rated water and dust resistant
- Super durable and highly protected against falls and impact.



Cloud management with high extensibility

- Pioneering ZKONG SaaS platform supports efficient collaboration of different devices across stores.
- pre-set system, plug and play.
- Support remote adjustment of display content, screen brightness, etc.
- NFC, Wi-Fi & Bluetooth



Safe & stable wired power supply

- Wired DC power
- Safe and durable customized power supply rail
- 40,000+h service life, green and eco-friendly



Free customization with rich accessories


- Hook, ring, holder and other various accessories.
- Adapt to a variety of shelves types and multi-scene application
- ZKONG own manufacturing base provides high quality products while minimizing costs.

TECH SPECIFICATION

EXAMPLARY PICTURE



TECHNICAL DRAWINGS (mm)





Display Features

Display Technology TFT

Active Display Area(mm) 135.36 (W) X 216.576 (H) mm (*2)

Resolution (Pixels) 800X1280 **Pixel Colors** Full color **Viewing Angle** 12 o'clock

Backlight White hight LED backlight

Brightness 400cd/m2

Usable Pages

Wireless

Operating Frequency

Encryption 128-bit AES **OTA** YES

Physical Features

DC powered Powered by

NFC YES **Operating Temperature** 25±5°C

Dimensions 243*150.1*14mm **Packaging Unit** 20 Labels/box

Compliance

Certification

CE,ROHS,FCC,MIC

2.4-2.485GHz